



# ROCKER COVER RACE RULES

## THE RACERS:

1. The racers cannot have any power source. Gravity only!
2. The rocker cover must be from any A Series
3. The racer shall not be more than 80 mm longer than the rocket cover
4. Racers shall have four wheels of not more than 155 mm diameter
5. Wheel track shall be not more than 210 mm
6. Maximum weight shall not exceed 3 kg
7. Speed is the aim and the fastest car should win out right, we are also looking for well-dressed tappet covers and this will be encouraged

## THE COURSE:

1. The decline will be 3.6 metres long followed by a run off area
2. The decline shall be divided into 2 lanes each 225 mm wide. The decline shall be 600 mm high at the rear most part. The front of the decline will be bevelled to give a smooth transition to the run-out area
3. A mechanical starting gate may be employed
4. The run-out section shall be of 2 lanes 900 mm wide. The lanes shall be clearly marked
5. The finish line shall be marked 1.5 metres from the front edge of the launch decline

## THE RACE:

1. There will be heats of 2 racers per heat
2. The racers will start with their front wheels on the start line. The first racer to have its front wheels cross the finish line is the winner. If neither racer makes it to the finish, the one going the furthest distance wins.
3. Any racer touching or crossing a lane marker shall be disqualified. The other racer becomes the winner

Winning racers will advance to the next round until all are eliminated except one which becomes the outright winner



Classic Sports Car Centre

